































		2'-0 $\frac{1}{2}$ " (622)	2'-4 $\frac{1}{2}$ " (724)	2'-6 $\frac{1}{2}$ " (775)	2'-8 $\frac{1}{2}$ " (826)	3'-0 $\frac{1}{2}$ " (927)	3'-2 $\frac{1}{2}$ " (978)
		2'-0"	2'-4"	2'-6"	2'-8"	3'-0"	3'-2"
		(610)	(711)	(762)	(813)	(914)	(965)
Rough Opening	Unit						
	Dimension						
4'-6 $\frac{1}{2}$ " (1384)	4'-6"						
5'-0 $\frac{1}{2}$ " (1537)	5'-0"						
5'-1 $\frac{1}{2}$ " (1562)	5'-1"						
5'-6 $\frac{1}{2}$ " (1689)	5'-6"						
6'-0 $\frac{1}{2}$ " (1842)	6'-0"						































Single Radius Single-Hung Reverse Cottage (RSHRC)

					
RSHRC2046	RSHRC2446	RSHRC2646	RSHRC2846	RSHRC3046	RSHRC3246
					
RSHRC2050	RSHRC2450	RSHRC2650	RSHRC2850	RSHRC3050	RSHRC3250
					
RSHRC2051	RSHRC2451	RSHRC2651	RSHRC2851	RSHRC3051	RSHRC3251
					
RSHRC2056	RSHRC2456	RSHRC2656	RSHRC2856	RSHRC3056	RSHRC3256
					
RSHRC2060	RSHRC2460	RSHRC2660	RSHRC2860	RSHRC3060	RSHRC3260

### Notes:

"Unit Dimension" always refers to outside frame to frame dimension.  
 "Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.  
 Dimensions in parentheses are in millimeters.  
 Units may be ordered with sash lifts, if desired. Units 3'-0" and wider will use two sash lifts.  
 Bottom sash operates up and down and tilts inward for cleaning. Top sash is fixed.  
 Default Radius for single units is 3'-0" (914). Contact your Andersen supplier for information on additional sizes.

Date: 1/17/17  
 Scale: 1/8" (3) = 1' (305)

Rough Opening		4'-0½"	4'-8½"	5'-0½"	5'-4½"	6'-0½"	6'-4½"
		(1232)	(1435)	(1537)	(1638)	(1842)	(1943)
Unit Dimension		4'-0"	4'-8"	5'-0"	5'-4"	6'-0"	6'-4"
		(1219)	(1422)	(1524)	(1626)	(1829)	(1930)
Twin Radius Single-Hung Reverse Cottage (RSHRC-2)							
4'-6½"	(1384)						
5'-0½"	(1537)						
5'-1½"	(1562)						
5'-6½"	(1689)						
6'-0"	(1829)						

### Notes:

"Unit Dimension" always refers to outside frame to frame dimension.

"Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

Dimensions in parentheses are in millimeters.

Units may be ordered with sash lifts, if desired. Units 3'-0" and wider will use two sash lifts.

Bottom sash operates up and down and tilts inward for cleaning. Top sash is fixed.

Default Radius for single units is 6'-0" (1829). Contact your Andersen supplier for information on additional sizes.

Date: 1/17/17

Scale: 1/8" (3) = 1' (305)