

Table of Gliding Window Sizes

Scale 1/8" (3) = 1'-0" (305) – 1:96

Window Dimension	2'-11 1/2" (902)	3'-11 1/2" (1207)	4'-11 1/2" (1511)	5'-11 1/2" (1816)
Minimum Rough Opening	3'-0" (914)	4'-0" (1219)	5'-0" (1524)	6'-0" (1829)
Unobstructed Glass (single sash only)	13 11/16" (348)	19 11/16" (500)	25 11/16" (652)	31 11/16" (805)

1'-5 1/2" (445)	1'-6" (457)	11 1/2" (292)		
244GW4016				
1'-11 1/2" (597)	2'-0" (610)	17 1/2" (445)		
244GW3020				
244GW4020				
2'-11 1/2" (902)	3'-0" (914)	29 1/2" (749)		
244GW3030		244GW4030		
244GW5030 [◊]		244GW6030 [◊]		
3'-5 1/2" (1054)	3'-6" (1067)	35 1/2" (902)		
244GW3036		244GW4036		
244GW5036 [◊]		244GW6036 [◊]		
3'-11 1/2" (1207)	4'-0" (1219)	41 1/2" (1054)		
244GW3040		244GW4040 [◊]		
244GW5040 [◊]		244GW6040 [◊]		
4'-5 1/2" (1359)	4'-6" (1372)	47 1/2" (1207)		
244GW4046 [◊]		244GW5046 [◊]		
244GW6046 [◊]				
4'-11 1/2" (1511)	5'-0" (1524)	53 1/2" (1359)		
244GW4050 [◊]		244GW5050 [◊]		
244GW6050 [◊]				



Active Stationary
Viewed from the exterior.

- "Window Dimension" always refers to outside frame to frame dimension.
- "Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
- Dimensions in parentheses are in millimeters.
- ◊ Meet or exceed clear opening area of 5.7 sq. ft. or 0.53 m², clear opening width of 20" (508) and clear opening height of 24" (610).