


**Table of Gliding Window Sizes**

Scale 1/8" (3) = 1'-0" (305) – 1:96

Window Dimension	2'-11 1/4" (895)	3'-11 1/4" (1200)	4'-11 1/4" (1505)	5'-11 1/4" (1810)
<b>Minimum Rough Opening</b>	3'-0" (914)	4'-0" (1219)	5'-0" (1524)	6'-0" (1829)
Unobstructed Glass (single sash only)	12 9/16" (319)	18 9/16" (472)	24 9/16" (624)	30 9/16" (776)
1'-10 1/4" (565)	1'-11" (584)	1'-11 1/8" (359)		
	<b>G32</b>	<b>G42</b>		
2'-11 1/4" (895)	3'-0" (914)	27 1/8" (689)		
	<b>G33</b>	<b>G43</b>	<b>G53</b>	<b>G63<sup>◊</sup></b>
3'-5 1/4" (1048)	3'-6" (1067)	33 1/8" (841)		
	<b>G336</b>	<b>G436</b>	<b>G536<sup>◊</sup></b>	<b>G636<sup>◊</sup></b>
3'-11 1/4" (1200)	4'-0" (1219)	39 1/8" (994)		
	<b>G34</b>	<b>G44<sup>◊</sup></b>	<b>G54<sup>◊</sup></b>	<b>G64<sup>◊</sup></b>
4'-11 1/4" (1505)	5'-0" (1524)	51 1/8" (1299)		
	<b>G35</b>	<b>G45<sup>◊</sup></b>	<b>G55<sup>◊</sup></b>	<b>G65<sup>◊</sup></b>



Viewed from the exterior.

- "Window Dimension" always refers to outside frame to frame dimension.
- **"Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.**
- Dimensions in parentheses are in millimeters.
- ◊ Meet or exceed clear opening area of 5.7 sq. ft. or 0.53 m<sup>2</sup>, clear opening width of 20" (508) and clear opening height of 24" (610).