Andersen® E-Series Awning Window Sizes

	2' 0 ¹ /2"	2' 4 1/2"	2' 6 ¹ /2"	2' 8 1/2"	3' 0 ¹ /2"	3' 4 ¹ /2"	4' 0 ¹ /2"
	2' 0"	2' 4"	2' 6"	2' 8"	3' 0"	3' 4"	4' 0"
1.8 1/2"	AWN2018	AWN2418	AWN2618	AWN2818	AWN3018	AWN3418	AWN4018
2' 0 1/2"	AWN2020	AWN2420	AWN2620	AWN2820	AWN3020	AWN3420	AWN4020
2' 6 1/2"	AWN2026	AWN2426	AWN2626	AWN2826	AWN3026	AWN3426	AWN4026
3' 0 1/2"	AWN2030	AWN2430	AWN2630	AWN2830	AWN3030	AWN3430	AWN4030
3'4"	AWN2034	AWN2434	AWN2634	AWN2834	AWN3034	AWN3434	AWN4030
4' 0 1/2"	AWN2040	AWN2440	AWN2640	AWN2840	AWN3040	AWN3440	AWN4040

Andersen® E-Series Push Out Awning Window Sizes

	2' 0 ¹ /2"	2' 4 1/2"	2' 6 ¹ / ₂ "	2' 8 1/2"	3' 0 ¹ /2"	3' 4 ¹ /2"	4' 0 ¹ /2"
	2' 0"	2' 4"	2' 6"	2' 8"	3' 0"	3' 4"	4' 0"
/3	/.5/ - `						
1.8 1/2"	PAWN2018	PAWN2418	PAWN2618	PAWN2818	PAWN3018	PAWN3418	PAWN4018
2' 0 1/2"	PAWN2020	PAWN2420	PAWN2620	PAWN2820	PAWN3020	PAWN3420	PAWN4020
2' 6 1/2" 2' 6"	PAWAIGOGG	PAWAIOAGO	DAWN 1999	PAWA 1999			PAWALION
3' 0 1/2"	PAWN2026	PAWN2426	PAWN2626	PAWN2826	PAWN3026	PAWN3426	PAWN4026
3' 4 1/2" 3' 4"	PAWN2030	PAWN2430	PAWN2630 PAWN2634	PAWN2830 PAWN2834	PAWN3030 PAWN3034	PAWN3430 PAWN3434	PAWN4030
4' 0 1/2" 4' 0"	PAWN2040	PAWN2440	PAWN2640	PAWN2840	PAWN3040		


NOTES

If glass is positioned within 18" of the finished floor, safety/tempered glass may be required. Local codes may differ. Verify tempered glass requirements with your local building code official.

Use structural mullions when necessary or required by code.

The light patterns illustrated apply to rectangular removable wood grilles, Modern Divided Lights, Classic Divided Lights, Deco 100, 150 and 400 and between-glass grilles. All removable wood grilles will be installed in the units unless otherwise specified.

For a metric conversion in millimeters, multiply dimensions in inches by 25.4.



FORMULA FOR COMBINATION WINDOWS

The overall frame dimension (both width and height) is equal to the sum of the individual unit frame dimensions plus mull dimension(s) .

The overall rough opening (both width and height) is equal to the overall frame dimensions plus 1/4" on all sides.

Any unit within each combination can be operating or fixed.

PUSH OUT AWNING

Units \geq 36" Actual Frame Height receive (2) friction stays.