

INSTALL MATERIALS

COIL STOCK

Roll aluminum that is bent into shape to form a transition piece between the unit exterior and siding/trim. Andersen offers a variety of colors to complement most exteriors.

FLASHING

Windows/Doors must be flashed to integrate the window/door into the drainage plane. Flashing must be applied shingle fashion to direct water to the exterior. Andersen offers straight and formable self-adhered flashing materials for use on any window or door project. The water management system may be of the drainage or barrier type.

BACKER ROD

Flexible foam product from Andersen that is used behind sealant to increase elasticity, reduce consumption, force the sealant into contact with the sides of the joint creating a better bond

DRIP CAP

One piece aluminum or vinyl cover installed above windows/doors that directs water away from the top of the unit.

SEALANT

Highly flexible, minimally shrinking Andersen sealant provides a watertight seal around windows, doors and trim.

SHIM

A wedge often made of wood used to plumb and/or level a window or door in the rough opening. Many professionals prefer Andersen shims that are made of plastic, flat and easily adjustable, and won't splinter or split.

FORMABLE SELF ADHERING SILL FLASHING

Windows/Doors must be flashed to integrate the window/door into the drainage plane. Flashing must be applied shingle fashion to direct water to the exterior. Andersen offers straight and formable self-adhered flashing materials for use on any window or door project. The water management system may be of the drainage or barrier type.

